US009636911B2

(12) **United States Patent**
Kurihara et al.

(10) **Patent No.: US 9,636,911 B2**
(45) **Date of Patent: May 2, 2017**

(54) **INKJET RECORDING DEVICE**

(71) Applicant: **Hitachi Industrial Equipment Systems Co., Ltd.**, Chiyoda-ku, Tokyo (JP)

(72) Inventors: **Hiroko Kurihara**, Tokyo (JP); **Takashi Kawano**, Tokyo (JP)

(73) Assignee: **Hitachi Industrial Equipment Systems Co., Ltd.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/108,893**

(22) PCT Filed: **Dec. 26, 2014**

(86) PCT No.: **PCT/JP2014/084639**

§ 371 (c)(1),
(2) Date: **Jun. 29, 2016**

(87) PCT Pub. No.: **WO2015/105031**

PCT Pub. Date: **Jul. 16, 2015**

(65) **Prior Publication Data**

US 2016/0325545 A1 Nov. 10, 2016

(30) **Foreign Application Priority Data**

Jan. 8, 2014 (JP) 2014-001637

(51) **Int. Cl.**
B41J 2/08 (2006.01)
B41J 2/12 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***B41J 2/04555*** (2013.01); ***B41J 2/02*** (2013.01); ***B41J 2/04586*** (2013.01); ***B41J 2/08*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B41J 2/175; B41J 2/02; B41J 2/07; B41J 2/08; B41J 2/085; B41J 2/09; B41J 2/04555; B41J 2/04586; B41J 2002/1853
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,310,846 A 1/1982 Horike
4,442,440 A * 4/1984 Elchinger B41J 2/185 347/74
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 645 245 A1 7/1994
JP 55-92984 A 7/1980
(Continued)

OTHER PUBLICATIONS

International Search Report (PCT/ISA/210) issued in PCT Application No. PCT/JP2014/084639 dated Mar. 24, 2015 with English translation (5 pages).
(Continued)

Primary Examiner — Anh T. N. Vo
(74) *Attorney, Agent, or Firm* — Crowell & Moring LLP

(57) **ABSTRACT**

The purpose of the present invention is to suppress variance in the print quality of an inkjet recording device. In order to solve the above problem, the present invention is an inkjet recording device of a charge control type equipped with two or more nozzles which are disposed side by side in a print head, the inkjet recording device being characterized by the following: having a control unit for performing print control independently for each of a plurality of printing configurations; the control unit having an input unit whereby current values of print elements of each of the printing configurations can be periodically checked, and having an output unit whereby the print elements during a subsequent print can be modified; and in that the control unit further adjusts each of
(Continued)